

Lubricant Additives Business

ROYCO[®] LGFAviation Hydraulic Fluid

Description

Royco[®] **LGF** is a mineral oil based hydraulic fluid designed specifically for use in aircraft landing gear systems, shock struts and other fluid dampening systems. Modern additive technology for greatly improved lubricity and extreme pressure anti-wear performance is used to provide the performance levels required by today's aircraft.

Application

Royco[®] LGF consists of hydraulic fluid conforming to MIL-PRF-5606 plus other additives to improve landing gear performance.

Features and Benefits

Royco[®] **LGF** is completely compatible with oils meeting MIL-PRF-5606. **Royco**[®] **LGF** was specifically developed to improve "slip stiction" and to alleviate "ladder cracking" in landing gear struts due to sudden and severe shock load encountered during landing.

Approvals and Specifications

ROYCO® LGF (yellow) is qualified to Boeing Materials Specification BMS 3-32 (Type II).

Technical data*

PROPERTIES	TEST METHOD	ROYCO [®] LGF
Kinematic Viscosity @ 40°C, cSt	ASTM D445	14.55
Acid Number, mg KOH/g	ASTM D974	2.7
API Gravity	ASTM D4052	30.05
Pounds per Gallon		7.292
Color, ASTM	ASTM D1500	1.3
Materials		Conforms

^{*}The analytical data are guide values.

Packaging

ROYCO® LGF is available in 55 gallon drums and 5 gallon pails. Other packaging may be available on request.

Handling

Page 1 of 2

Edition: 2020-10-26





Lubricant Additives Business

ROYCO[®] LGFAviation Hydraulic Fluid

Consult product safety data sheet (SDS) for additional handling information on ROYCO® LGF

This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2020 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

North America +1.833.LANXESS customer.care@lanxess.com Europe, Middle East & Africa +44.161.875.3800 emea.export@lanxess.com South & Central America +55.19.3522.5083 atendimento.cliente@lanxess.com Asia Pacific +86.21.6109.6666 Orders.apac@lanxess.com

Page 2 of 2

Edition: 2020-10-26

